

## IN THE CLAIM

Please cancel Claims 1 to 5, without prejudice or disclaimer of the subject matter thereof, and add new claims 6 to 9. The added new claim 6 is based on the original claims 1 and 2 and the features in Fig. 1 of the present invention (we add some description about the strip 25, hole 251 and the button 252 and the related connections of these elements, which are shown in the Fig. 1). The new claim 7, 8, and 9 add features same as the original claim 3, 4 and 5, respectively, to the new claims 6. Thereby, it is assured that the new claims are based on the original claim and specification and thus no new matter is added. The relation of the new claims with respect to the original claims are shown in the following REMARK. Examiners can read the claims more easily from the REMARK.

## **LIST OF CLAIMS:**

Claims 1 to 5 (Cancelled)

Claim 6. (New claim) A safety bag with a firm structure formed by connecting a hard casing and a soft enclosure so as to form a bag body with an opening; the soft enclosure having belts for being carried on the shoulders of users; a cover extending from the soft enclosure for covering the opening; the connections of the hard casing and soft enclosure being formed at two sides of the bag and being enclosed by connectors;

wherein the connectors are installed with a plurality of buckles; the cover is installed with a first insertion portion at a front surface of the bag and a second insertion portion at two sides of the bag; a band passes through the first insertion portion and second insertion portion and then winds around an edge of the cover; a strip having one end fixed to the cover and another end having a hole; a retaining ring is installed at a position that the band is out of the first insertion portion; thereby, the band out of the first insertion portion and second insertion portion firstly passes

through the hole of the strip and then is tightened by the retaining ring; two ends of the band are buckled to selective two buckles of the plurality of buckles; thereby, the cover is firmly secured to the hard casing so as to prevent objects in the bag from falling down; and

a front outer side of the enclosure has a buckle button so that when the cover covers the opening of the enclosure, the buckle button can be further buckled to the hole so as to fix the cover to the enclosure; further the band also passes through the hole and then is confined by the retaining ring;

wherein the band is capable of being buckled to the buckles of different levels so that the tightness of the cover securing to the hard casing is adjusted according to the objects in the bag.

wherein the inner side of the soft enclosure is installed with a hidden bag for receiving valuable objects; the hidden bag is fixed at one lateral side of the enclosure and only.

Claim 7. (New claim) The safety bag with a firm structure as claimed in claim 6, wherein a top of the soft enclosure is installed with a handle.

Claim 8. (New claim) The safety bag with a firm structure as claimed in claim 6, wherein a top of the soft enclosure is installed with a handle.

Claim 9. (New claim) The safety bag with a firm structure as claimed in claim 6, wherein a first connector is at an outer side of the bag and is made of leather materials, and a second connector is at an inner side of the bag and is made of metals.